

For
INDUSTRIAL
PRODUCT



Visco Inter Pratama
print your colorful life

Versatile Flatbed UV Printer





VROOM
—UV DIGITAL PRINTER—

NEWEST Model 2019

NC-UV0690PEIII

NOCAL
—Digital printer—

Creating More Value



//Advantageous features



Water Proof, UV Proof and Scratch Proof

Finished products is Water Proof, UV Proof, and Scratch proof finished product is suitable for outdoor use.



Automatic anti-static system

Automatic anti-static design to avoid satellite ink drops flying which causes resulting in poor print quality



Fast print image with white and color

The printing machine can print white ink and color ink print together/print simultaneously. (White + Color / Color + White)



White ink recirculation system

White ink recirculation system results in an effective elimination of ink starvation, deposition and protects print head from clogging hazard.



Paper



Carpet



Glass



Plastic



Ceramic



Acrylic



Wood



Plastic


Advanced mechanical structure
assists value-added print product

NC-UV0690PEIII

Efficient printing style

With 3pcs heads will be able to print white, color inks and varnish at once, time saving

3D embossed effect;
Embossed & varnish effect
heart touching print effect



TECHNICAL SPECIFICATION

Model	NC-UV0690PEIII	
Print Head	3 pcs Heads EPSON DXII Micro Piezo (Nozzle 180*6)	
Resolution	360dpi, 720dpi, 1440dpi	
Print mode color	CMYKLCm+W+V (Varnish) / CMYKLCm+W / CMYK+W	
Ink	UV (UV curing ink)	
Ink supply system	Continuous Ink Supply System (CISS)	
Max. material thickness	0-130mm	
Drying system	UV (LED UV Lamp)	
Media handling	Flatbed	
Printing size / Printing Weight	Max. 610mm(W) x 900mm(L) / Approx. 20 kg	
Printing speed	1440*720dpi 8pass 6sqm/hour	
Media	Glass, Ceramic tile, Metal, Paper, Leather, Wallpaper, Wood, Soft Film, PVC, Acrylic, PP, PE, Aluminium, Bamboo, Form Board, Plastic, etc	
X/Y/Z-axis motors	Servo motors controlled + mute linear guideways	
Control System	Microsoft Windows 7, 10 (32/64bit) with RAM > 4Gb	
RIP Software	Photoprint I2	
Image format	TIF, JPG, EPS, PDF, PNG, BMP, PSD, AI	
Power Supply	220V(±10%); AC.50Hz/60Hz >400W	
Operation environment	Temperature	20°C ~ 25°C
	Humidity	15% ~ 20%
Printer Dimension (L x W x H)	1550mm x 1680mm x 620mm	
Package dimension (L x W x H)	1750mm x 1880mm x 850mm	
Net Weight / Gross Weight	155Kg / 260Kg	

Above specifications are subject to change without prior notice.

We also sale Print Head Solvent and Eco Solvent



Visco Inter Pratama

Address: Jalan Hasyim Ashari No. 64, Jakarta Pusat - 10140, Indonesia

Phone : (+62 21) 6331050 - 6331051

Email : visco.ip88@gmail.com

Website : www.viscoip.com

Service Center : Yogyakarta, Surabaya, Makasar

